



Model	SSL-92	SSL-94	SSL-96	SSL-98	SSL-910	SSL-912
Solar Panel	Monocrystalline glass lamination	Monocrystalline glass lamination	Monocrystalline glass lamination	Monocrystalline glass lamination	Monocrystalline glass lamination	Monocrystalline glass lamination
Battery Type	18650 NCM	18650 NCM	18650 NCM	18650 NCM	18650 NCM	18650 NCM
Charging temperature control	YES	YES	YES	YES	YES	YES
CCT	4000K	4000K	4000K	4000K	4000K	4000K
Luminous flux.Max	2000lm	4000lm	6000lm	8000lm	10000lm	12000lm
PIR Angle	120°	120°	120°	120°	120°	120°
PIR Distance	8m	8m	8m	8m	8m	8m
Diameter	Φ60	Φ60	Φ60	Φ60	Φ60	Φ60
Install Height / Distance.Max	3m/15m	4m/18m	6m/27m	8m/36m	10m/45m	12m/54m
IP / IK	IP65 / IK08	IP65 / IK08	IP65 / IK08	IP65 / IK08	IP65 / IK08	IP65 / IK08
Charging temperature	0~45℃	0~45℃	0~45℃	0~45℃	0~45℃	0~45℃
Discharging temperature	-20~+60℃	-20~+60℃	-20~+60℃	-20~+60℃	-20~+60℃	-20~+60℃